

# ICP-PCMCIA Dual-Slot CompactPCI Card-Bus Host Adaptor

PN: OSS-CPCI-3U-CR-PCMCIA



## Features

- Dual slot PCMCIA adapter, holds two type I/II or one type III card
- Driver software for Windows 98 and Windows 2000
- Compatible with Windows 98 and 2000 operating systems
- System Soft software is needed when using this carrier in WindowsNT
- This PCMCIA carrier will work only with an Inova CPU board.

## Specifications

CompactPCI:	32-bit/33 MHz with bus-master DMA, interrupt levels INTA & INTB support, 3.3V/5.0V signaling voltage and full Plug & Play compatibility
PCMCIA Slots:	2 type I, II or 1 type III
Voltage:	5V DC or LV (3.3V DC)
Connector:	68-pin Card-Bus header
Supply:	VCC output current: 600mA (max.) @ 5V 1A (max.) @ 3.3V Short-circuit limit: 2.2A (max.) VPP output current: 60mA (max.) @ 12V Short-circuit limit: 400mA
Mass:	151g (empty)
Size:	100mm x 160mm, single slot (3U, 4TE)
Operating Temperature:	0°C to +70°C
Storage Temperature:	-40°C to +85°C
Humidity:	5% to 95% (non-condensing) @ 40°C
Warranty:	Three-year limited warranty
Conformance:	CompactPCI R2.1 CE