

# CPCIe x4 Host Cable Adapter

3U CPCIe Type 2 host cable adapter installs in a CPCIe IO slot to connect to a downstream PCIe device or expansion system.

PN: OSS-CPCIe-3U-HIB2-x4

## Features

- PCI Express x4 cable connector on face plate
- Power on/cable present LEDs
- No Software Drivers Required
- PICMG EXP.0 system slot compliant
- x4 PCI Express PCI-SIG compliant cable uplink
- 10 Gbps cable bandwidth
- 3U or 6U form factor



## Specifications

<b>Dimensions:</b>	(H x L) 3.939 x 6.299"
<b>Front Panel Connectors:</b>	One PCIe x4 cable connector
<b>Front Panel Indicators:</b>	Power On / Cable Present LEDs
<b>Re-driver:</b>	Pericom PI2EQX4402D
<b>Temperature Range:</b>	0° to 50°C (32° to 122°F)
<b>Relative Humidity:</b>	10 to 90% non-condensing
<b>Shock:</b>	30g acceleration peak (11ms pulse)
<b>Vibration:</b>	5-17 Hz 0.5" double amplitude displacement; 7-2000Hz, 1.5g acceleration
<b>Power Consumption:</b>	3.75W typical, 3.3@1.3A
<b>Agency Compliance:</b>	FCC Class B CE RoHS