

2U Compute Accelerator with AMD FirePro S9170 GPUs

The CA4003 Compute Accelerator with four AMD FirePro S9170 GPU accelerators is employed in a variety of HPC applications including oil and gas exploration and financial services. Completely integrated with the GPUs most suited for a specific application, it's easy installation and tested reliability makes it superior to alternative products. The CA4003 occupies only 2U of rack space and connects directly to one or two host server(s) through the latest technology PCIe x16 Gen3 connection.

PN: OSS-PCIe3-2UX

Features

- 2U High
- One or two Rear Panel PCIe x16 Gen3 Interfaces
- Remote System Monitoring Capability; monitor fans, temperature and voltages
- Dual redundant 1620-watt Power Supplies
- Superior Cooling with five temperature controlled fans
- Choice of 1 to 4 AMD FirePro S9170 GPUs



Specifications

Enclosure	
Dimensions	3.5"H x 17"W x 22.25" D Removable front bezel with air filter Front Panel LEDs
Capacity	Up to 4 AMD FirePro S9170 GPUs
Power Supply	Dual redundant 1620W power supply (removable)
Expansion	One or two PCIe x16 1-meter cable(s) One or two PCIe x16 Gen3 cable adapter(s)
Cooling	Four 132 CFM fans (removable)
Operating Environment	1-35°C 10-90% relative humidity 0-10,000 feet above sea level
Storing Environment	-40 to 85°C Any relative humidity 0-50,000 feet above sea level
Agency Compliance	Pending: FCC Class A CE RoHS

	AMD FirePro S9170
GPU	Single "Hawaii" XL GT44
Compute Units	44
GDDR5 Memory	32GB
Memory Bandwidth	320 GB/s
Peak Performance	5.24 Tflops SP 2.62 Tflops DP
Compute and Graphics progressing	Full OpenGL acceleration
Total Board Power	275W